



APC BK350EI

APC Back-UPS CS · Specification summary



Capacity	350VA
Output power	210W
Form factor	Tower
Nominal voltage	230V
Output outlets	4x IEC C13
Battery	User Replaceable
Main input voltage	230 V AC 1 phase
Input connection	IEC 60320 C14
Maximum input current	7 A
Switching current capacity	7 A
Efficiency at full load	180...266 V
Input frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	210 W
Rated power in VA	350 VA
Output connection	3 IEC 60320 C13, 1 IEC 60320 C13 surge, 2 IEC 60320
Type of USB power supply	None
Maximum configurable power in VA	350 VA
Maximum configurable power in W	210 W
Transfer time	6 ms typical : 10 ms maximum
UPS topology	Standby
Output frequency	47...63 Hz sync to mains, 50/60 Hz +/- 1 Hz unsynchronised
Replacement battery	RBC2
Battery capacity	7.0 Ah
Battery type	Lead-acid internal included

Control panel	LED Status display with on line : on battery
Free slot	0
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone, alarm
Software Compatibility	SmartConnect
UPS connectivity	USB port
Surge energy rating	310 J
Noise filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping, response time : meets UL 1449
Cable length	1.16 m
Number of cables	2
Color	Beige
Height	165 mm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-bk350ei.html>