



APC BK650-AS

APC Back-UPS CS · Specification summary



Capacity	650VA
Output power	400W
Form factor	Tower
Nominal voltage	230V
Output outlets	4x IEC C13
Battery	User Replaceable
Main input voltage	230 V AC 1 phase
Input connection	IEC 60320 C14
Efficiency at full load	160...282 V adjustable, 180...260 V
Input frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	400 W
Rated power in VA	650 VA
Output connection	3 IEC 60320 C13, 1 IEC 60320 C13 surge
Type of USB power supply	None
Maximum configurable power in VA	650 VA
Maximum configurable power in W	400 W
UPS topology	Standby
Waveform type	Stepped approximation to a sinewave
Replacement battery	RBC17
Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone, alarm
Software Compatibility	SmartConnect
UPS connectivity	USB port

Surge energy rating	320 J
Cable length	1.8 m
Number of cables	2
Color	Beige
Height	165 mm
Width	91 mm
Depth	284 mm
Product weight	6.04 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-bk650-as.html>