



APC SBP20KRM14U

Service Bypass Panel · Specification summary



Nominal voltage	230V
Rated current	125A
Input connections	2x hardwire input connectors
Output connections	8x IEC 60320 C19
Main Input Voltage	220 V, 230 V, 240 V, 380 V 3 phases, 400 V 3 phases, 415 V 3 phases
Product or component type	Bypass kit
Main Output Voltage	230 V
Other Output Voltage	220 V, 240 V
Number of rack unit	4U
Number of cables	1
Provided equipment	Installation guide, Rack mounting brackets, User manual
Range of product	Smart-UPS Accessories
Colour	Black
Height	178 mm
Width	432 mm
Depth	572 mm
Net weight	18.78 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E), 1 hard wire 5 wire (3P + N + E)
Max line current	125 A
Input current limits	125 A
Load capacity	20000 VA
Power factor	0...1
Max current draw	125 A
Number of power socket outlets	8 IEC 60320 C19
Protection type	Circuit breaker

Ambient air temperature for operation	-20...50 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-40...65 °C
Storage Relative Humidity	0...95 %

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-sbp20krmi4u.html>