



APC SBP3000

Service Bypass Panel · Specification summary



Voltage range	100-240V
Rated current	30A
Bypass switching	BBM
Input connection	Hardwire
Output connection	Hardwire
Form factor	2U rack-mount
Main Input Voltage	100 V, 120 V, 230 V
Product or Component Type	Bypass kit
Main Output Voltage	100 V, 120 V, 230 V
Other Output Voltage	110 V
Output connector type	Hard Wire 3-wire (H N + E) for 1 zone(s)
Number of rack unit	2U
Provided Equipment	Installation guide, Rack Mounting brackets, User Manual
Range of Product	Maintenance Bypass Panels
Color	Black
Height	3.5 in (89 mm)
Width	17.008 in (432 mm)
Depth	25 in (635 mm)
Net Weight	26.5 lb(US) (12 kg)
Mounting Support	Wall
Mounting preference	No preference
Mounting Mode	Rack-mounted with kit
Input Frequency	50/60 Hz
Number of input connectors	1 Hard Wire 3-wire (H N + E)
Max line current	30 A
Input current limits	30 A
Power factor	0...1
Max current draw	30 A
Protection Type	Circuit breaker
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)

Relative Humidity	0...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	-40...149 °F (-40...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0...15240 m)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-sbp3000.html>