



APC SBP3000RMHW

Service Bypass PDU · Specification summary



Nominal voltage	230V
Rated current	16AMP
Connection type	Hardwire
Mounting accessories	Rack mounting brackets
Main Input Voltage	230 V
Product or component type	Bypass kit
Main Output Voltage	230 V
Output connector type	Hard wire 3-wire (H N + E) for 1 zone(s)
Number of rack unit	2U
Provided equipment	User manual, Rack mounting brackets
Range of product	Maintenance Bypass Panels
Colour	Black
Height	89 mm
Width	432 mm
Depth	76 mm
Net weight	2.27 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Network frequency	50/60 Hz
permissible voltage	220...240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3000 VA
Power factor	0...1
Max current draw	16 A
Number of power socket outlets	1 IEC Jumpers
Protection type	Circuit breaker
Power cable length	1.00 m
Ambient air temperature for operation	0...40 °C

Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-sbp3000rmhw.html>