



APC SBP5000RMI2U

Service Bypass Panel · Specification summary



Nominal voltage	230V
Maximum current	32A
Bypass type	BBM
Input connection	IEC320 C20/HW
Output connections	(2) C19 (8) C13
Rack height	2U
Main Input Voltage	230 V
Product or component type	Bypass kit
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	2U
Number of cables	1
Provided equipment	Hardwire panel, Installation guide, Rack mounting brackets, User manual, Wall mounting brackets
Range of product	Maintenance Bypass Panels
Colour	Black
Height	89 mm
Width	432 mm
Depth	660 mm
Net weight	11.36 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Max line current	32 A
Input current limits	32 A
Load capacity	7680 VA
Power factor	0...1
Max current draw	32 A

Number of power socket outlets	8 IEC 60320 C13, 2 IEC 60320 C19
Protection type	Circuit breaker
Ambient air temperature for operation	-20...50 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-sbp5000rmi2u.html>