



APC SRT10KXLI

On-Line Tower UPS · Specification summary



Power capacity	10000 VA
Maximum configurable power	10000 W
Nominal output voltage	230 V
Topology	Double conversion online
Waveform type	Sine wave
Form factor	Tower
Main input voltage	230 V AC 1 phase, 380 V AC 3 phase, 400 V AC 3 phase, 415 V AC 3 phase
Other input voltage	220 V, 240 V, 380 V, 415 V
Efficiency at full load	100...275 V adjustable (half load), 173...476 V adjustable (half load)
Input connection	1 Hard Wire 3-wire (1PH+N+G), 1 Hard Wire 5-wire (3PH + N + G)
Input frequency	40 - 70 Hz auto-sensing
Output voltage	230 V 1 phase
Other output voltage	220 V, 240 V
Rated power in W	10000 W
Rated power in VA	10000 VA
Output connection	6 IEC 60320, 3 IEC Jumpers, 4 IEC 60320
Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	10000 VA
Maximum configurable power in W	10000 W
UPS topology	On-Line
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC140, , SRT192BP2US, , SRT192RMBPUS

Battery type	Lead-acid internal included
Emergency power off	Yes
Free slot	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port, USB port, Embedded network management card 3, Available expansion slot
Surge energy rating	480 J
Color	Black
Height	17.008 in (432 mm)
Width	10.4 in (263 mm)
Depth	28.1 in (715 mm)
Product weight	246.52 lb(US) (111.82 kg)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-srt10kxli.html>