



APC SRT3000RMXLI

On-Line Uninterruptible Power Supply (UPS) · Specification summary



Rated power	3kVA/2.7kW
Topology	Double-conversion on-line
Waveform	Pure sine wave
Nominal voltage	230V
Form factor	Rackmount 2U
Mounting	Rack/Tower convertible
Main input voltage	230 V AC 1 phase
Other input voltage	220 V, 240 V
Input connection	BS 1363 British, IEC 60320 C20, CEE 7/7
Efficiency at full load	100...275 V adjustable (half load)
Input frequency	40...70 Hz auto-sensing
Output voltage	230 V AC 1 phase
Other output voltage	220 V, 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Output connection	8 IEC 60320, 2 IEC Jumpers, 2 IEC 60320
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
UPS topology	On-Line
Waveform type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC152
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery type	Lead-acid internal included
Emergency power off	Yes
Free slot	1

Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port, USB port
Surge energy rating	340 J
Number of rack unit	2U
Cable length	2.4 m
Number of cables	1
Color	Black

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-srt3000rmxli.html>