



APC SURT023M

Marine UPS Filter · Specification summary



Load capacity	3000 VA
Input voltages	208V, 220V, 230V, 240V
Rack height	1U
Main Input Voltage	208 V, 220 V, 230 V, 240 V
Product or Component Type	Filter
Main Output Voltage	200 V, 208 V, 220 V, 230 V, 240 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Cable length	8 ft (2.4 m)
Number of cables	1
Color	Black
Height	1.7 in (44 mm)
Width	17.008 in (432 mm)
Depth	11.0 in (279 mm)
Net Weight	11.22 lb(US) (5.09 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Input Frequency	47...63 Hz
Max line current	16 A
Input current limits	16 A
permissible voltage	100...240 V
Max current draw	16 A
Ambient Air Temperature for Operation	32...131 °F (0...55 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...167 °F (-25...75 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0...15240 m)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-apc-power-surt023m.html>