



# Baofeng BF-T26

FRS Two-Way Radio · Specification summary



|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| Frequency range                | FRS (exact frequency not specified)                                   |
| Transmit power                 | 2W                                                                    |
| Battery                        | 3.7V battery                                                          |
| Key features                   | USB-C charging; VOX; Emergency alarm; Simplex operation               |
| Dimensions / weight            | 110×56×16mm (without antenna); 110g (with battery)                    |
| Working temperature            | -10°C to +50°C                                                        |
| Operation Voltage              | DC 3.7 V ±10%                                                         |
| Operation Mode                 | Simplex                                                               |
| Dimensions                     | 110mm×56mm×16mm (without Antenna)                                     |
| Weight                         | 110g (Battery pack included)                                          |
| Antenna Impedance              | 50ohm                                                                 |
| RF Output Power                | 2W                                                                    |
| FM Modulation                  | 11K0F3E@12.5KHz                                                       |
| Adjacent Channel Power         | 60dB @ 12.5KHz                                                        |
| Transmission current           | ≤1200mA                                                               |
| Receive Sensitivity            | 0.25μV (12dB SINAD)                                                   |
| Adjacent Channel Selectivity   | ≥55dB@12.5KHz                                                         |
| Inter Modulation and Rejection | ≥55dB@12.5KHz                                                         |
| Conducted Spurious Emission    | ≤-57dB@12.5KHz                                                        |
| Rated Audio Power Output       | 0.75W @8 ohms                                                         |
| Receive current                | ≤380mA                                                                |
| Rated Audio Distortion         | ≤5%                                                                   |
| NOTE                           | All specifications may be modified without prior notice or liability. |

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

