



Baofeng GT-3 Mark II

Analog VHF/UHF Dual-Band Handheld Radio · Specification summary



Frequency range	VHF 144-148 MHz; UHF 420-450 MHz
Transmit power	5W
Channels	128
Battery	7.4V 1800mAh Li-ion
Key features	Dual Watch; VOX; CTCSS/DCS; DTMF; Emergency Alert
Burst Tones	Press PTT+ A/B to generate 1750Hz Press PTT + Band to generate 2100Hz
Output Power	5 Watts
Memory channels	Up to 128 channels
Frequency stability	2.5ppm
Antenna impedance	50 ohm
Operating temperature	-20 ~ +60 °C
Supply Voltage	Rechargeable Lithium-Ion mAh 7.4V/1800
Consumption	in standby:≤73mA, in reception:380mA, in transmission:≤1.4A
Mode of operation	Simplex or semi-duplex
Antenna Type	Compatible with SMA-Female Antenna
Earpiece & Programming Type	Compatible with K-plug earpiece/cable

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-baofeng-walkie-talkie-gt-3-mark-ii.html>