



Baofeng GT-3TP Mark III

Analog VHF/UHF Dual-Band Handheld Radio · Specification summary



Frequency range	VHF 144-148 MHz; UHF 420-450 MHz (3800mAh version)
Transmit power	8W/4W/1W
Channels	128
Battery	7.4V 3800mAh Li-ion (3800mAh version)
Ingress protection	Dustproof shell; IP rating not specified
Key features	VOX; Repeater Offset; High-Gain Antenna; LED Flashlight; Adjustable Squelch
Tri-Power	High / Med / Low Power (8W/4W/1W)
Big buttons & knob	GT-3TP has a built-in PTT key, CALL key, and MONI key on the left side of the radio
Antenna Interface	Fine copper antenna connector outperforms previous antenna connectors and improves communications.
Radio Frequency IC	Upgraded Squelch enhances interference rejection
FM Receiver Chip	The RDA5802N has a powerful low-IF digital audio processor. This makes it have optimum sound quality with varying reception conditions.
Power Amplifier IC	Low crossover distortion, Low quiescent circuit current. Provides plenty of clean, clear receive audio.
LED Flashlight	high lumen output
Shell	Upgraded shell: Dustproof
Mode of operation	Simplex or semi-duplex
Memory channels	Up to 128
Frequency stability	2.5ppm
Antenna impedance	50 ohm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
<https://www.isdsb.com.my/product-baofeng-walkie-talkie-gt-3tp-mark-iii.html>