



Baofeng GT-5R Pro

Analog Multi-Band Handheld Radio · Specification summary



Frequency range	TX 136-174/220-260/400-480 MHz (product specification); RX 88-108 FM/108-136 AM/136-174/220-260/350-390/400-520 MHz; regional restrictions apply
Transmit power	5W
Channels	128
Battery	7.4V 1800mAh Li-ion
Key features	Multi-Band Reception; Airband Reception; NOAA Weather Reception; VOX; Dual Standby
Dimensions / weight	55 x 106 x 28 mm; 208g
Receiver Frequency	FM 88-108 MHz;AM 108-136MHz(VFO-Only),VHF 136-174MHz,220-260MHz(VFO-Only),UHF350-390MHz,400-520MHz(VFO-Only),[EU FM 88-108MHz; VHF & UHF]
Transmission Frequency	136-174 & 220-260 & 400-480 MHz
Power Supply	Li-Ion battery, 7.4V/1800 mAh (BL-5)
Memory Channels	128
Operating Temperature	-10°C to +45°C
Working Mode	Monoband/Dualband
Modulation	F3E (FM)
Max. Frequency Deviation	≤ ±5 KHz
Spurious Radiation	< -60 dB
Frequency Stability	±2.5 ppm
Rx Sensitivity	< 0.2 uV
Audio Output Power	≥ 500 mW
Dimensions	55 x 106 x 28 mm / 2.2 x 4.2 x 1.1 in (LxAxP)
Weight	208g / 7.3oz

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-baofeng-walkie-talkie-gt-5r-pro.html>