



Baofeng UV-25 Plus

Analog Tri-Band Handheld Two-Way Radio with GPS · Specification summary



Frequency range	TX: 136-174 / 220-260 / 400-520 MHz; RX: FM 65-108 / AM 108-136 / 136-174 / 220-260 / 350-390 / 400-520 MHz
Transmit power	10W; High/Medium/Low selectable
Channels	1000 channels / 10 zones
Battery	7.4V 5200mAh Li-ion; USB-C charging
Key features	GPS positioning and sharing; One-key frequency copy; Fall detection alert; NOAA reception; 2-inch color display
Dimensions / weight	181×69×44 mm; 590g
Receiver Frequency	FM 65-108 MHz; AM 108-136MHz(VFO-Only), VHF 136-174MHz, 220-260MHz(VFO-Only), UHF350-390MHz, 400-520MHz(VFO-Only)
Transmission Frequency	136-174 MHz & 220-260 MHz & 400-520 MHz
Channel Spacing	25.0 KHz (Wide)/12.5 KHz (Narrow)
Memory Channel	1,000 [10 Zones]
Operation Voltage	DC 7.4 V ±10%
Operating Temperature	-10°C to 60°C
Antenna Impedance	50 Ohm
Frequency Stability	±2.5 ppm
Spurious Emission	-16 dBm1GHz
Audio Distortion	≤5%
Rated Audio Power Output	1W @16 ohms
Connection for Accessories	2-pin Kenwood jack
Dimensions	7.1 x 2.7 x 1.8" / 181 x 69 x 44mm
Weight	0.59kg / 1.3lb
GPS-Compatible Models	UV-28 Plus

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-baofeng-walkie-talkie-uv-25-plus.html>