



Baofeng UV-28 Plus

Analog Tri-Band Handheld Two-Way Radio with GPS · Specification summary



Frequency range	TX: 136-174 / 220-260 / 400-520 MHz (US); 144-146 / 430-440 MHz (EU); RX: FM 65-108 / AM 108-136 / 136-174 / 220-260 / 350-390 / 400-520 MHz
Transmit power	10W
Channels	1000 channels / 10 zones
Battery	2200mAh rechargeable battery; USB-C charging
Key features	Bluetooth APP programming; GPS location sharing; One-key frequency copy; DTMF manual dial; 1.77-inch TFT display
Dimensions / weight	157×67×43 mm; 360g
Transmission Frequency	136-174 MHz& 220-260 MHz & 400-520 MHz, [EU 144-146 & 430-440 MHz]
Receiver Frequency	FM 65-108 MHz; AM 108-136MHz, VHF 136-174MHz, 220-260MHz, UHF350-390MHz, 400-520MHz, [EU FM 65-108 MHz; AM 108-136MHz, VHF & UHF]
Channel Spacing	25.0 KHz (Wide)/12.5 KHz (Narrow)
Memory Channel	1,000 Channels / 10 zones
Operation Voltage	DC 7.4 V ±10%
Operating Temperature	-10°C to 60°C
Antenna Impedance	50Ω
Frequency Stability	±2.5 ppm
Spurious Emission	-16 dBm1GHz
Audio Distortion	≤5%
Rated Audio Power Output	0.75 Watts @ 16 Ω
Connection for Accessories	2-pin Kenwood jack
Dimensions	6.2 x 2.6 x 1.7" / 157 X 67 X 43mm
Weight	0.36kg / 0.79lb
GPS-Compatible Models	UV-25 Plus

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

