Bird-X Ultrason X (USX)

Ultrasonic Bird Deterrent with Separate Control Box · Specification summary



Coverage	Up to 3,600 sq ft (approx. 334 m²) with all four speakers
Coverage per frequency setting	Low: 900 sq ft (84 m²) per speaker; Medium: 675 sq ft (63 m²) per speaker; High: 570 sq ft (53 m²) per speaker
Frequency	15–25 kHz, selectable High / Medium / Low
Speakers	4 × speakers, 8 ohms, 30 W
Speaker cable	100 ft (approx. 30 m) per speaker
Sound pressure	95–102 dB per speaker at 1 m
Speaker sequence	Each speaker broadcasts for 2 seconds, then switches to the next speaker
Power requirements	110 VAC adapter (220 VAC adapter available)
Dimensions	Control unit 9" × 9" × 5"; speakers 4" × 4" × 6"
Weight	15 lb (approx. 6.8 kg)
Kit contents	Control unit, power adapter, mounting hardware and four speakers
Target pests	Birds (pigeons, sparrows, starlings, crows, blackbirds, grackles, seagulls, swallows), bats, rodents
Applications	Gas stations, parking lots, hotels, restaurants, balconies, patios, manufacturing or warehouse facilities, airports
Installation	Wall, post or other vertical surface; semi-enclosed and outdoor use, weather resistant
Compliance	Supply power source UL and CE listed; EPA Est. 075130-OR-001
SKU	USX

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-bird-x-bird-control-ultrason-x-usx.html