



Chuango KP-700

· Specification summary

Device class	Wireless Keypad
Function reference	Wireless alarm keypad for arming and disarming a compatible alarm system by code. The manufacturer also describes an electronic-lock arrangement and optional RFID tags; lock hardware and power must be checked separately.
RFID tag capacity	Up to 50 RFID tags are listed as supported. This is capacity, not 50 included tags or compatibility with every RFID credential.
Power arrangement	Three AAA batteries or 12 V DC are listed as alternative supplies. Confirm the actual supply, installation and battery contents; this is not a lock-load or lock-power rating.
Battery-powered static current	At most 3 μ A, explicitly qualified by the manufacturer as battery-powered operation. Do not apply this value to the 12 V supply or calculate a guaranteed battery life.
Transmitting current	At most 10 mA is listed for transmitting current; this is not an electronic-lock load rating.
Radio-version reference	315 MHz or 433.92 MHz are listed as alternatives. Confirm the supplied version and matching controller; one unit is not thereby approved for both bands.
Transmitting-range reference	At most 80 m transmitting distance in an open area. No installed through-wall range is guaranteed.
Temperature reference	-10 to 55 °C.
Humidity reference	At most 80% relative humidity, non-condensing.
Housing reference	ABS plastic.
Body dimensions	135 × 90 × 15 mm (L × W × H).
Net-weight reference	90 g is listed as net weight. This is not shipping or packed weight.

Specifications are summarised from the manufacturer's published information (checked 2026-10-21). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-chuango-alarm-wireless-kp-700.html>