



Chuango RC-80

· Specification summary

Device class	Remote Control
Function reference	Alarm remote control for arming, disarming and an SOS panic function. Match it to the actual alarm controller.
Power reference	3 V DC using one CR2025 lithium cell. Do not substitute a different coin-cell type or assume a battery-life rating.
Alarm-current reference	At most 7 mA in the manufacturer Alarm Current row.
Radio-version reference	315 MHz or 433.92 MHz are listed as alternatives. Confirm the supplied version and a matching controller; do not assume one device operates both bands.
Transmitting-range reference	At most 80 m in an open area. This is not a guaranteed indoor, through-wall or interference-limited distance.
Housing reference	PC+ABS plastic.
Temperature reference	-10 to 55 °C.
Humidity reference	At most 80% relative humidity, non-condensing. This does not establish an outdoor ingress-protection rating.
Body dimensions	58 × 31 × 9.5 mm (L × W × H).

Specifications are summarised from the manufacturer's published information (checked 2026-10-21). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-chuango-alarm-system-rc-80-chuango-rc-80-remote-control.html>