D-Link DES-F1026P-E



250M 24-Port Fast Ethernet PoE Switch · Specification summary

Ports	24 × 10/100 Mbps PoE ports, 1 × Gigabit uplink port, 1 × Gigabit combo uplink (RJ-45 / SFP)
PoE Budget	250 W
PoE-Capable Ports	Ports 1-24 (ports 1-8 up to 250 m at 10 Mbps with Extend enabled)
Data Transfer Rates	Gigabit Ethernet, Fast Ethernet (100 Mbps), Ethernet (10 Mbps)
Media Interface Exchange	Auto MDI/MDI-X adjustment on all ports
Switching Fabric	6.8 Gbps
Transmission Method	Store-and-forward
Smart Features	Extend, VLAN, QoS and PoE
Lightning Protection	6 kV
Operating Temperature	0 to 40 °C (32 to 104 °F)
Operating Humidity	0% to 95% RH non-condensing
Size	Desktop (with mounting kit)
Dimensions	440 × 180 × 44 mm
Weight	2.8 kg
Safety	LVD
EMI/EMC	CE, FCC

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-d-link-network-des-f1026p-e.html