# D-Link DGS-F1100-26PSD-SI

26-Port Layer 2 Gigabit Cloud Managed PoE Switch · Specification summary



| | |
|---|---|
| **Network Interface** | 24 × 10/100/1000 Mbps PoE ports (ports 1-24), 1 × 1000 Mbps RJ-45 port, 2 × Gigabit SFP ports |
| **Management Port** | RJ-45 port |
| **Standards** | IEEE 802.3 10BASE-T, 802.3u 100BASE-TX, 802.3ab 1000BASE-T, 802.3z 1000BASE-X, 802.3x flow control |
| **PoE Protocol** | IEEE 802.3af (up to 15.4 W), IEEE 802.3at (up to 30 W) |
| **PoE Ports** | Ports 1-24, up to 30 W per port |
| **Power Budget** | 350 W |
| **Switching Capacity** | 52 Gbps |
| **Packet Forwarding** | 38.688 Mpps |
| **CPU Memory** | DDR3 128 MB |
| **Flash Memory** | 32 MB |
| **LED Indicators** | Per port: Link/ACT, PoE; per device: Power, SYS, RST |
| **Dimensions** | 440 × 180 × 44 mm |
| **Housing** | Metal |
| **Power Input** | AC 100-240 V, 50/60 Hz |
| **Fan** | 1 |
| **Operating Temperature** | 0 to 40 °C (32 to 104 °F) |
| **Storage Temperature** | -10 to 70 °C (14 to 158 °F) |
| **Operating Humidity** | 10% to 90% (non-condensing) |
| **Lightning Protection** | 6 kV |
| **Certifications** | CE |

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-d-link-network-dgs-f1100-26psd-si.html