D-Link DLA-X303

D-Lite Cloud-Managed AX3000 Outdoor Access Point · Specification summary



Device Interfaces	1 × RJ45 10/100/1000 Mbps WAN Ethernet (with PoE), 1 × RJ45 10/100/1000 Mbps LAN Ethernet, reset button, power jack
CPU	Quad-core 1 GHz
Memory	DDR3L 512 MB
Flash	128 MB NAND flash
Power Supply	PoE or 12 V / 1 A DC
Antenna	2 × 5 dBi internal 2.4 GHz antennas, 2 × 7 dBi internal 5.8 GHz antennas
Wi-Fi	2T2R 2.4 GHz 802.11b/g/n/ac/ax, 573.5 Mbps; 2T2R 5.8 GHz 802.11a/n/ac/ax, 2402 Mbps
Max Transmit Power	29 dBm (26 dBm per chain), 2.4 GHz and 5 GHz
Concurrent Clients	500+ concurrent Wi-Fi client devices
Dimensions	235.5 × 100.7 × 70 mm
Weight	530 g
Operating Temperature	-30 °C to 60 °C
Humidity	5% to 95% (typical)
MTBF	> 250,000 hours
Mounting Options	Wall / pole mount
IP Rating	IP67
Certifications	CE, UL, RoHS

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-d-link-network-dla-x303.html