D-Link DXS-1210-16TC

10 Gigabit Smart Managed Switch · Specification summary



Interfaces	12 × 100M/1G/2.5G/5G/10GBASE-T ports, 2 × 10G SFP+ ports, 2 × 1G/10GBASE-T/SFP+ combo ports
Console Port	RJ-45 console port
Switching Capacity	320 Gbps
Max. Packet Forwarding Rate	238.08 Mpps
Transmission Method	Store-and-forward
MAC Address Table	Up to 32,000 entries per device
AC Input	100 to 240 VAC
Max. Power Consumption	64.2 W
Standby Power Consumption	31.7 W
Fan	3 fans
Acoustics	Max. 50.4 dB, min. 39.7 dB
Operating Temperature	-5 to 50 °C (23 to 122 °F)
Operating Humidity	0% to 95% non-condensing
Dimensions (L × W × H)	440 × 210 × 44 mm
Weight	3.123 kg
Hardware Version	B1

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-d-link-network-dxs-1210-16tc.html