D-Link DXS-F108T

8-Port 10G Web Management Switch · Specification summary



Interface	8 × 10G RJ45 ports (100M/1G/2.5G/5G/10G)
Port Standards	IEEE 802.3, 802.3i, 802.3u, 802.3ab, 802.3x, 802.3az, 802.3ae, 802.3bz
Switching Capacity	160 Gbps
Packet Forwarding Rate	119.04 Mpps
Packet Buffer	12 Mbit
MAC Address Table	16K
Jumbo Frame	Supported
VLAN	Access / Trunk / Hybrid; Q-in-Q; VLAN range 1-4094, up to 4K active VLANs
Transmission Method	Store and forward
Surge Protection	Common mode 6 kV (Class C); ESD air 8 kV, contact 6 kV (Class C)
Power Supply	AC 100-240 V 50/60 Hz; DC 12 V 8 A
Mainboard Power Consumption	13.8 W
Multicast	IGMP snooping (v1/v2/v3), router port, static IGMP join
QoS	SP and WRR scheduling, 802.1p and DSCP priority, up to 8 queues per port
Product Dimensions	320 × 207 × 45 mm
Net Weight	1.82 kg
Fan	1
Installation	Desktop
Operating Temperature	0 to 40 °C
Operating Humidity	10% to 90%, non-condensing
Package Contents	Switch, power cord, instruction manual

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-d-link-network-dxs-f108t.html