



# EZVIZ L2S

Smart fingerprint door lock, not a camera · Specification summary



|                                                        |                                                                                                                          |
|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| <b>Manufacturer model code</b>                         | CS-L2S-11FCP                                                                                                             |
| <b>Panel size</b>                                      | 307 × 74 × 32 mm (12.09 × 2.91 × 1.26 inch)                                                                              |
| <b>Panel material</b>                                  | Aluminum alloy                                                                                                           |
| <b>Lock body type</b>                                  | Mechanical lock body                                                                                                     |
| <b>Fingerprint sensor</b>                              | Semiconductor                                                                                                            |
| <b>Built-in doorbell</b>                               | Supports                                                                                                                 |
| <b>Operating temperature</b>                           | -25 °C to 70 °C                                                                                                          |
| <b>Operation humidity</b>                              | Humidity 95% or less (non-condensing)                                                                                    |
| <b>Suitable door types</b>                             | Supports using with wooden and iron doors                                                                                |
| <b>Lock face plate (installed on the door)</b>         | Standard 240 × 24 mm, double-holes, rectangular angle                                                                    |
| <b>Lock strike plate (installed on the door frame)</b> | For a wooden door: standard 30 × 218 mm<br>For an iron door: standard 30 × 260 mm                                        |
| <b>Supported door thickness</b>                        | Use with doors that are 40 to 110 mm thick (standard wooden door of 40 to 55 mm; standard iron door of 55 to 75 mm)      |
| <b>Door handle direction</b>                           | Supports handle setup to be right-handed or left-handed                                                                  |
| <b>Fingerprints</b>                                    | Up to 50 fingerprints                                                                                                    |
| <b>Passwords</b>                                       | Up to 50 sets of passwords; supports anti-peeping virtual passwords; supports creating temporary passcodes via EZVIZ App |
| <b>Proximity cards</b>                                 | Up to 50 EZVIZ door cards, with a recommended reading distance of 0 to 10 mm                                             |
| <b>Mechanical keys</b>                                 | Supports mechanical keys for emergency unlocking                                                                         |
| <b>Cylinder</b>                                        | C grade lock cylinder                                                                                                    |
| <b>Indoor lock</b>                                     | Supports                                                                                                                 |
| <b>Handle safety lock</b>                              | Supports                                                                                                                 |
| <b>Anti-tamper alarm</b>                               | Supports                                                                                                                 |
| <b>Failed attempts auto-lock</b>                       | Auto-disable for 3 minutes after 5 failed unlocking attempts                                                             |
| <b>Working power</b>                                   | Uses four 1.5V AA alkaline batteries                                                                                     |
| <b>Time of use</b>                                     | Up to 1 year based on the usage of 10 openings per day                                                                   |
| <b>Low battery alarm</b>                               | Supports                                                                                                                 |

|                                |                                                                                                                                                                                                                                           |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Emergency power supply</b>  | Micro-USB power bank                                                                                                                                                                                                                      |
| <b>Communication method</b>    | Zigbee 3.0                                                                                                                                                                                                                                |
| <b>User access management</b>  | Supports                                                                                                                                                                                                                                  |
| <b>Temporary password</b>      | Supports                                                                                                                                                                                                                                  |
| <b>Privacy mode</b>            | Supports                                                                                                                                                                                                                                  |
| <b>Real-time mobile alerts</b> | Supports                                                                                                                                                                                                                                  |
| <b>Door status time log</b>    | Supports                                                                                                                                                                                                                                  |
| <b>In the box</b>              | L2S Smart Fingerprint Lock (Front Panel + Rear Panel); Lock Body; Gateway; AA Alkaline Batteries (4); Proximity Cards (2); Mechanical Keys (2); Square Rod; Drilling Template; Standard Screw Kit; Lock Body Screw Kit; Quick Start Guide |
| <b>Certifications</b>          | CE / FCC / RoSH                                                                                                                                                                                                                           |

Specifications are summarised from the manufacturer's published information (checked 2026-10-27). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-ezviz-camera-l2s.html>