Hikvision AE-MN7083(RJ45)

Mobile Network Video Recorder · Specification summary



IP Camera	8-ch connected via PoE interfaces
Video Compression	H.265, H.264
Audio Compression	G.711a/G.711u/G.722.1/G.726
Two-way Audio	1, integrated in EXT.DEV interface
Video Output	Main output: 1, integrated in EXT.DEV interface. VGA: 1
HDD/SSD	2 × 2.5 inch HDD/SSD, SSD up to 4 TB, HDD up to 2 TB
SD Card Storage	1 × SD card, up to 512 GB
Dial-up	1 × 4G card slot, 1 × FAKRA antenna
Network Interface	Front panel: 1 × 10M/100M RJ45, Rear panel: 1 × 10M/100M RJ45
Alarm Input	4 high/low level signal inputs, 1 pulse signal input, 1 BUTTON input
Alarm Output	2 relay signal outputs
Positioning	GPS & GLONASS
Product Dimension	202 mm × 267.6 mm × 93.9 mm
Power Supply	+9 to +36 VDC

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-camera-ae-mn7083-rj45.html