



Hikvision DS-2CD2D25G1/M-D/NF

· Specification summary



Device class	2 MP Mini Network Camera
Image sensor	1/2.8" Progressive Scan CMOS
Max. resolution	1920 × 1080
Min. illumination	Color: 0.002 Lux @ (F1.2, AGC ON)
Shutter time	1/3 s to 1/100,000 s
Wide dynamic range	120 dB
Lens options (Available Model)	2.8 mm / 4 mm
Lens mount	M12
Video compression	Main stream: H.265/H.264; Sub-stream: H.265/H.264/MJPEG; Third stream: H.265/H.264
Audio type	Mono
Audio interface	1 input (line in)
Simultaneous live view	Up to 15 channels
Ethernet interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
Smart event	Intrusion detection, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection
Client	iVMS-4200, Hik-Connect
Power	12 VDC ± 20%, 0.13 A, max. 1.5 W, Ø 5.5 mm coaxial power plug
Material	Zinc alloy
Dimension	31.5 mm × 31.5 mm × 49.6 mm (1.2" × 1.2" × 2")
Weight	Approx. 93 g (0.2 lb.)
Startup and operating conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)

Specifications are summarised from the manufacturer's published information (checked 2026-10-23). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-camera-ds-2cd2d25g1-m-d-nf.html>