Hikvision DS-2CD6365G0-IS

6 MP IR Network Fisheye Camera · Specification summary



Image Sensor	1/1.8" Progressive Scan CMOS
Max Resolution	3072 × 2048
Lens	1.27 mm, F2.6, horizontal FOV 173° (wall mount), 360° (ceiling mount), 360° (table mount)
IR Range	Up to 15 m
Video Compression	Main stream H.265+/H.265/H.264+/H.264, sub stream H.265/H.264/MJPEG
Power Supply	12 VDC ± 25%, 0.9 A, max. 11 W; PoE 802.3af, class 0, 36 to 57 V, max. 12.95 W
Interface	1 RJ45 10 M/100 M/1000 M self-adaptive Ethernet port
Dimensions	167.4 × 152.8 × 50 mm
Operating Temperature	-40 °C to +60 °C
Storage	microSD/microSDHC/microSDXC/TF card, up to 256 GB

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-camera-ds-2cd6365g0-is.html