Hikvision DS-2XC3786G0H-LIZSU/SL(PA)(27135)O-STD

Polymer 8MP Anti-Corrosion PTRZ Dome · Specification summary



Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	3840 × 2160
Min. Illumination	Color: 0.0028 Lux @ (F1.2, AGC ON), 0 Lux with light
Lens	Varifocal lens, motorized lens, 2.7 to 13.5 mm (horizontal FOV 112.3° to 41.2°)
Aperture	Max. F1.2
Supplement Light	IR, White Light, up to 40 m
Video Compression	Main stream: H.265/H.264/H.264+/H.265+
Video Bit Rate	32 Kbps to 16 Mbps
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
Built-in Microphone	Yes, 2 built-in microphones
Power	12 VDC ± 25%, 1.5 A, max. 18 W / PoE: IEEE 802.3at, Class 4, max. 21 W
Startup and Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F)
Dimension	Ø154.9 mm × 128.53 mm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-camera-ds-2xc3786g0h-lizsu-sl-pa-27135-o-std.html