Hikvision DS-3E3700-H

Layer 3 Ethernet Switch Series · Specification summary



Models in Datasheet	DS-3E3728-H, DS-3E3728F-H, DS-3E3752-H
Service Ports (DS-3E3728-H)	24 × 10/100/1000BASE-T (including 8 combo), 4 × 10G/1G BASE-X SFP+
Service Ports (DS-3E3728F-H)	24 × SFP (including 8 combo), 4 × 10G/1G BASE-X SFP+
Service Ports (DS-3E3752-H)	48 × 10/100/1000BASE-T, 4 × 10G/1G BASE-X SFP+
Expansion	1 expansion slot, 2 fan tray slots, 2 power module slots
Switching Capacity	Whole device 598 Gbps
Packet Forwarding Rate	Whole device 444.91 Mpps
Dimensions (W × D × H)	440 × 360 × 43.6 mm
Input Voltage	AC 100 to 240 V, 50/60 Hz; DC -48 to -60 V
Power Module	150 W AC or 150 W DC

Specifications are summarised from the manufacturer's published information (checked 2026-10-25). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-hikvision-network-ds-3e3700-h.html