Hikvision DS-3WAP5112E-EI

Wi-Fi 5 1200M Wall-Plate Access Point · Specification summary



Wireless Standard	Wi-Fi 5
Wireless Speed	Max: 1167 Mbps (2.4G: 300 Mbps, 5G: 867 Mbps)
Working Frequency Band	Radio 1: 5G (11a/n/ac), Radio 2: 2.4G (11b/g/n)
Ports	1× 10/100 Mbps PoE in port, 1 × 10/100 Mbps RJ45 port
Power Supply Method	PoE power supply: IEEE 802.3af, IEEE 802.3at
Maximum Power Consumption	9.5 W
Max. Number of Connected Clients	128
Antenna	Integrated 2.4 GHz and 5 GHz: 2 built-in omnidirectional antennas
Product Dimensions (W × H × D)	86 mm × 86 mm × 29.9 mm
Mounting	In-Wall Mounting
Working Temperature	0°C to 40°C (32°F to 104°F)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-network-ds-3wap5112e-ei.html