Hikvision DS-3WAP5212E-EI

Wi-Fi 5 1200M Ceiling Access Point · Specification summary



Wireless Standard	Wi-Fi 5
Wireless Speed	Max: 1167 Mbps (2.4G: 300 Mbps, 5G: 867 Mbps)
Working Frequency Band	Radio 1: 5G (11a/n/ac), Radio 2: 2.4G (11b/g/n)
Ports	1× 10/100 Mbps PoE in port, 1 × 10/100 Mbps RJ45 port
Power Supply Method	DC power supply: 12 V, 1.5 A / PoE power supply: IEEE 802.3at
Maximum Power Consumption	18 W
Max. Number of Connected Clients	128
Antenna	2.4 GHz: 2 built-in omnidirectional antennas, 5 GHz: 2 built-in omnidirectional antennas
Product Dimensions	Ø220 mm × 49.7 mm (excluding bracket)
Mounting	Ceiling Mounting
Working Temperature	0°C to 40°C (32°F to 104°F)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-network-ds-3wap5212e-ei.html