Hikvision DS-7716NI-I4

16-ch 1.5U 4K NVR · Specification summary



IP Video Input	16-ch, up to 12 MP resolution
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	256 Mbps
Decoding Format	H.265/H.265+/H.264/H.264+/MPEG4
Decoding Capability	1-ch@32 MP (30 fps)/2-ch@12 MP (20 fps)/4-ch@8 MP (25 fps)/8-ch@4 MP (30 fps)/16-ch@1080p (30 fps)
Network Interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
SATA	4 SATA interfaces
Capacity	Up to 10 TB capacity for each HDD
Alarm In/Out	16/4 (16/8 is optional)
Power Supply	100 to 240 VAC, 50 to 60 Hz
Consumption	≤ 20 W (without HDD)
Working Temperature	-10 to +55 ºC (+14 to +131 ºF)
Chassis	19-inch rack-mounted 1.5U chassis
Dimension (W × D × H)	445 × 400 × 75 mm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-hikvision-nvr-ds-7716ni-i4.html