



# Hikvision DS-D2065LU-Y

· Specification summary

|                                                            |                                                                                                                                                 |
|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Device class</b>                                        | LCD Display                                                                                                                                     |
| <b>Screen size</b>                                         | 65 inch                                                                                                                                         |
| <b>Active display area</b>                                 | 1428.48 mm (horizontal) × 803.52 mm (vertical); not the complete display dimensions.                                                            |
| <b>Backlight</b>                                           | Direct-lit LED backlight                                                                                                                        |
| <b>Pixel pitch</b>                                         | 0.372 mm                                                                                                                                        |
| <b>Bezel width</b>                                         | 2.3 mm (top/left), 1.2 mm (bottom/right)                                                                                                        |
| <b>Native resolution</b>                                   | 3840 × 2160 at 60 Hz, downward compatible as listed; source timing must be checked.                                                             |
| <b>Brightness</b>                                          | 500 cd/m <sup>2</sup> as listed                                                                                                                 |
| <b>Viewing angle</b>                                       | 178° horizontal and 178° vertical                                                                                                               |
| <b>Color depth</b>                                         | 8 bit, 16.7M as listed                                                                                                                          |
| <b>Physical seam</b>                                       | 3.5 mm as listed; not the width of each individual bezel edge.                                                                                  |
| <b>Contrast ratio</b>                                      | 1200:1                                                                                                                                          |
| <b>Response time</b>                                       | 10 ms                                                                                                                                           |
| <b>Color gamut</b>                                         | 72% NTSC                                                                                                                                        |
| <b>Surface declaration</b>                                 | Haze 25%, 3H as listed; no additional test standard is inferred.                                                                                |
| <b>HDMI output</b>                                         | HDMI × 1, as listed; confirm the required source and display-chain arrangement.                                                                 |
| <b>Serial control</b>                                      | RS232 IN × 1 and RS232 OUT × 1; serial control does not establish Ethernet or PoE.                                                              |
| <b>Reserved-port notice</b>                                | USB and LAN are marked reserved in the cited physical-interface table. No usable USB media, touch, charging or network function is established. |
| <b>Power input</b>                                         | 100–240 VAC, 50/60 Hz                                                                                                                           |
| <b>Power consumption</b>                                   | ≤260 W as listed                                                                                                                                |
| <b>Standby consumption</b>                                 | ≤0.5 W                                                                                                                                          |
| <b>Operating temperature</b>                               | 0°C to 40°C (32°F to 104°F)                                                                                                                     |
| <b>Operating humidity</b>                                  | 10% RH to 80% RH, non-condensing                                                                                                                |
| <b>Storage temperature</b>                                 | –20°C to 60°C (–4°F to 140°F)                                                                                                                   |
| <b>Storage humidity</b>                                    | 10% RH to 90% RH, non-condensing                                                                                                                |
| <b>VESA pattern</b>                                        | 800 mm (horizontal) × 600 mm (vertical); matching the hole pattern alone does not approve a bracket.                                            |
| <b>Panel dimensions in specification table (W × H × D)</b> | 1432.58 × 807.62 × 85.1 mm; not an installed bracket or cable-clearance envelope.                                                               |

|                                         |                                                                                                                                                                            |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Package dimensions (W × H × D)</b>   | 1630 × 1013 × 302 mm for a carton with one display; not the panel dimensions.                                                                                              |
| <b>Net weight</b>                       | 29.2 ± 0.5 kg for a single display                                                                                                                                         |
| <b>Gross weight</b>                     | 59.4 ± 0.5 kg for a carton with one display                                                                                                                                |
| <b>Casing material</b>                  | SECC, as listed                                                                                                                                                            |
| <b>Optional mounting references</b>     | DS-DN65B1M/F (modular frame), DS-DN65B1M/B (modular base), DS-DN6500W/U (wall-mounted bracket), DS-DN6501W (wall-mounted bracket). All are optional, not assumed included. |
| <b>Manufacturer lifecycle reference</b> | The retained manufacturer page was marked “Discontinued” when checked on 19 October 2026. This is not a statement of ISD stock or replacement availability.                |

Specifications are summarised from the manufacturer's published information (checked 2026-10-19). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-display-ds-d2065lu-y.html>