



Hikvision DS-D5019QE-B

· Specification summary

Device class	Monitor
Maximum resolution	1366 × 768 as listed; no native refresh rate or Full HD claim is established here.
Brightness	200 cd/m ² as listed
Contrast ratio	600:1
Response time	5 ms
Color count	16.7M as listed; no unstated bit depth is inferred.
Active display area	409.8 × 230.4 mm; not the complete casing dimensions.
Backlight	LED backlight
Pixel pitch	0.300 mm (horizontal) × 0.300 mm (vertical)
Power input	100–240 VAC, 50/60 Hz
HDMI input	1 HDMI input; version and source timing require confirmation.
VGA input	1 VGA input
Operating temperature	0°C to 40°C (32°F to 104°F)
Operating humidity	10% to 85%, non-condensing
Storage temperature	–20°C to 55°C (–4°F to 131°F)
Storage humidity	5% to 95%, non-condensing
VESA pattern	75 × 75 mm, 4-M4 as listed; confirm the complete bracket and fixing requirements.
Gross weight	3.5 kg
Net weight	2.8 kg
Casing color	Black
Optional wall-mount reference	DS-DM1940W is listed as an optional wall-mounted bracket. Confirm the exact unit and mounting assembly; it is not assumed supplied.

Specifications are summarised from the manufacturer's published information (checked 2026-10-19). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-commercial-display-ds-d5019qe-b.html>