



Hikvision DS-D5022FC

· Specification summary

Backlight	LED Backlight
Screen Size	21.5 inch
Pixel Pitch	0.248 mm (H) × 0.248 mm (V)
Resolution	1920×1080@60Hz
Brightness	250 cd/m ²
Contrast Ratio	1000: 1
Response Time	5 ms
Color Depth	16.7M
Active Display Area	476.64mm× 268.11mm
Viewing Angle	Horizontal 170°, vertical 160°
Reliability	24/7 operation
USB	1
Loudspeaker	2 × 2 W
Video Inputs	HDMI × 1; VGA × 1
BNC Input / Output	In × 1; Out × 1
Stereo Input / Output	In × 1; Out × 1
Power Supply	DC12V/3.0A
Power Consumption	≤30W
Standby Consumption	≤ 0.5 W
Working Temperature	0 to 40 ° C (32 to 104 ° F)
Working Humidity	10 to 85 %
Storage Temperature	-20 to 55 ° C (-4 to 131 ° F)
Storage Humidity	5 to 95%
Casing Color	Black
VESA	M4, 100 mm × 100 mm
Package Dimensions (W × H × D)	565mm×435mm×105mm
Gross Weight	4.6Kg
Net Weight	3.2kg
Packing List	VGA cable × 1; Power cord × 1; User manual × 1; Adapter × 1; Base bracket × 1; warranty card × 1
Wall mount	Optional DS-DM1940W

Dimensions with base (W x H x D)	511 x 377 x 170 mm
---	--------------------

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-commercial-display-ds-d5022fc.html>