



Hikvision DS-D5043F3-1V0S

· Specification summary



Screen Size	43 inch
Resolution	1920 × 1080 @60 Hz
Backlight	D-LED
Pixel Pitch	0.49005 (H) × 0.49005 (V) mm
Brightness	300 cd/m ²
Viewing Angle	178° / 178°
Color Depth	8 bit
Contrast Ratio	4000 : 1
Response Time	6.5 ms (typ)
Refresh Rate	60 Hz
Haze	25%
Color Gamut	72% NTSC
Reliability	7 * 24H
Data Transmission Interface	USB2.0 × 1
Control Interface	None
Loudspeaker	2 built-in speakers; wattage pending confirmation
Video Inputs	VGA × 1; HDMI 1.4 × 1
Audio Output	Line Out × 1
Power Supply	100~240 VAC, 50/60Hz, 1.0 A Max
Power Consumption	≤80W
Standby Consumption	≤ 0.5 W
Working Humidity	20% to 90% RH (Non-Condensing)
Storage Humidity	5% to 90% RH (Non-Condensing)
Casing Material	Plastic
VESA	200 mm × 200 mm(4 - M6 × 8 mm)
Bezel Width	1.1 mm (top/left/right) , 24 mm (bottom)
Product Dimensions (W × H × D)	Without base:954.3(W) mm × 561.65(H) mm × 76.06(D) mm 37.57(W) inch × 22.11 (H) inch × 2.99 (D) inch, With base:954.3(W) mm × 616.21(H) mm × 242.11(D) mm 37.57 (W) inch × 24.26 (H) inch × 9.53 (D) inch

Package Dimensions (W × H × D)	1073(W)mm×668(H)mm×161(D) mm (42.24 (W) × 26.3 (H) × 6.34 (D)) inch
Net Weight	6.85 ± 0.5 kg (15.10 ± 1.1 lb.)
Gross Weight	9.98 ± 0.5 kg (22.00 ± 1.1 lb.)
Optional mounting accessories	DS-DM4255W (optional)
Packing List	Monitor × 1, Base component × 1, Power cable × 1, HDMI cable (1.5 m) × 1, User manual × 1, Multilingual manual × 1, Remote control × 1, Screw × 6

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-commercial-display-ds-d5043f3-1v0s.html>