



Hikvision DS-D5043FC

· Specification summary

Documented equipment	Monitor
Listed maximum resolution	1920 × 1080 at 60 Hz, as listed; confirm the source timing.
Backlight	LED backlight
Response time	8 ms, as listed
Color count	16.7M, as listed; no unstated panel bit depth is inferred.
Viewing angle	178° horizontal and 178° vertical, as listed
Aspect ratio	16:9
HDMI input	1 HDMI input; version and source timing require confirmation.
VGA input	1 VGA input
DVI input	1 DVI input; confirm the connected source and cable requirements.
BNC input	1 BNC input; confirm signal format and compatibility.
Audio input	1 L/R audio input, 3.5 mm mini-jack as listed; confirm the connected signal level.
Power input	100–240 VAC, 50/60 Hz
Operating temperature	0°C to 40°C (32°F to 104°F)
Operating humidity	20% to 80% RH, non-condensing
Storage humidity	10% to 90% RH, non-condensing
Casing color	Black
VESA pattern and threads	200 × 300 mm pattern, 4-M6 threads; confirm the panel load, complete bracket and fixings.
Package dimensions (W × H × D)	1200 × 785 × 210 mm; carton dimensions, not the display or installed envelope.
Optional mounting references	DS-DM4255W wall mount and DS-DM4302B base bracket are listed as optional. Neither is assumed included; confirm the exact mounting assembly.
Manufacturer usage declaration	24/7 operation, as listed on the cited page; not a warranty, lifetime or site-specific uptime guarantee.
Manufacturer lifecycle reference	The cited manufacturer page was marked “Discontinued” when checked on 19 October 2026. This is not confirmation of ISD stock or replacement availability.

Specifications are summarised from the manufacturer's published information (checked 2026-10-19). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-commercial-display-ds-d5043fc.html>