



# Hikvision DS-D5065UC

· Specification summary

|                                                    |                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Documented equipment</b>                        | 65-inch TFT color LCD, as listed in the exact model section; no metric-diagonal conversion is inferred.                                                                                                                                                                                                                                                                               |
| <b>Maximum resolution</b>                          | 3840 × 2160 at 60 Hz, as listed; not a 4K-at-75-Hz declaration.                                                                                                                                                                                                                                                                                                                       |
| <b>Input frequency ranges</b>                      | Horizontal: 30–83 kHz; vertical: 56–75 Hz, as listed. These input ranges do not establish 4K operation at 75 Hz.                                                                                                                                                                                                                                                                      |
| <b>Display color</b>                               | 1.07 billion, as listed; native panel bit depth or FRC is not established by this cell.                                                                                                                                                                                                                                                                                               |
| <b>Pixel distance</b>                              | 0.372 mm (H) × 0.372 mm (V), as listed                                                                                                                                                                                                                                                                                                                                                |
| <b>Maximum display area</b>                        | 1428.48 mm horizontal × 803.52 mm vertical, as listed; not case dimensions or installed clearance.                                                                                                                                                                                                                                                                                    |
| <b>Input connector types</b>                       | 15-pin D-Sub and 19-pin HDMI, as listed; check the actual source cable and port.                                                                                                                                                                                                                                                                                                      |
| <b>HDMI inputs</b>                                 | 2 named HDMI video/audio inputs: HDMI 1 and HDMI 2. Confirm the required source timing and actual port configuration.                                                                                                                                                                                                                                                                 |
| <b>VGA input</b>                                   | 1 named D-Sub VGA video input                                                                                                                                                                                                                                                                                                                                                         |
| <b>Audio input</b>                                 | 1 named AUDIO IN connector; confirm the input signal and connector requirements.                                                                                                                                                                                                                                                                                                      |
| <b>Audio output</b>                                | 1 named AUDIO OUT connector, described as analogue audio output; confirm the connected equipment.                                                                                                                                                                                                                                                                                     |
| <b>HDMI 4K video-mode reference</b>                | The manual's HDMI video table includes progressive 3840 × 2160 at 60, 30, 25 and 24 Hz. Confirm the actual source, cable and selected HDMI mode; these are not VGA timings.                                                                                                                                                                                                           |
| <b>Factory-function limitations</b>                | The manual marks LAN, RS232 and Micro SD unavailable when leaving the factory. USB 2.0 is marked unavailable after leaving the factory; USB 3.0 is described for system-software updates. Android, CMS and USB-media remote functions are also marked unavailable when leaving the factory. Confirm actual enabled functions; a drawn port or menu is not an enabled-feature promise. |
| <b>Power input</b>                                 | 100–240 VAC, 50/60 Hz; confirm the actual unit label and supply arrangement.                                                                                                                                                                                                                                                                                                          |
| <b>Power-consumption declarations</b>              | Startup: 270 W maximum and 170 W typical. Standby: < 0.5 W. Shutdown: < 0.5 W. These are separate source operating states, not a site-specific load or uptime guarantee.                                                                                                                                                                                                              |
| <b>Operating &amp; storage environment</b>         | Operating: 0°C to 40°C and 20% to 80% humidity. Storage: –20°C to 60°C and 10% to 90% humidity. No additional condensation rating is established by this cell.                                                                                                                                                                                                                        |
| <b>Product dimensions without base (W × H × D)</b> | 1458.7 × 834.7 × 81.6 mm without base, as listed; not packed or installed-clearance dimensions.                                                                                                                                                                                                                                                                                       |
| <b>Net weight</b>                                  | 24.5 kg, as listed; not shipment weight or a mounting-load approval.                                                                                                                                                                                                                                                                                                                  |

Specifications are summarised from the manufacturer's published information (checked 2026-10-19). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price,

availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-commercial-display-ds-d5065uc.html>