



Hikvision DS-D5B65RB/EL

· Specification summary



Device class	Interactive Flat Panel
Screen size	65 inch
Native resolution	3840 × 2160 at 60 Hz
Brightness	400 cd/m ² typical
Touch technology	Infrared touch screen
Touch points	40-point multi-touch as listed; no per-operating-system touch-point capacity is established.
Touch response time	<10 ms
Touch precision	±1 mm within at least 90% of the touching area
Built-in operating system	Android 13.0; this does not establish Windows, OPS inclusion or Google/EDLA certification.
Built-in memory	4 GB
Built-in storage	32 GB
CPU	Cortex-A55 × 4 at 1.92 GHz
GPU	Mali-G52 MP2 (2EE)
Built-in loudspeakers	2 × 15 W
Bluetooth declaration	Built-in BLE (Bluetooth Low Energy) module supports Bluetooth 5.1, as listed.
Network interfaces	LAN 100 Mbps × 2 and Wi-Fi AP & Station; no PoE or unlisted wireless band/rate is assumed.
Data interfaces	USB 3.0 × 4, USB 2.0 × 1 and Type-C × 1. Type-C only supports USB 2.0 in this declaration; video input, charging or full-function Type-C is not assumed.
NFC declaration	Reader, as listed; supported card types and access-control functions are not established.
Video and audio inputs	HDMI 2.0 input × 2 and Audio In × 1
Audio output	Audio Out × 1; no HDMI video output is established by this row.
Control interfaces	TOUCH-USB 2.0 × 1 and RS232 × 1
Power input	100-240 VAC, 50/60 Hz
Standby consumption	0.5 W, as listed; not operating power consumption.
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating humidity	10% to 90% RH as listed; no additional condensation condition is inferred.

Specifications are summarised from the manufacturer's published information (checked 2026-10-19). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-commercial-display-ds-d5b65rb-el.html>