



Hikvision DS-K1T323EBWX-E1

Face access terminal · Specification summary



Credential	Face and EM card
Card frequency	125 kHz
Face capacity	1,000
Card capacity	3,000
Operating system	Linux
Screen size	2.4-inch
Resolution	240 × 320
Type	TFT
Operation method	Non touchable
Lens	× 1
Video standard	PAL (Default) and NTSC
Bluetooth	Support
Wired network	10/100 Mbps self adaptive
Wi-Fi	Support
PoE	IEEE802.3at, standard PoE
Wiegand	1, supports Wiegand input, single direction
User capacity	1000
Event capacity	150000
Card type	EM card
Card reading frequency	125 KHz
Face recognition duration	□ 0.33 s
Face recognition accuracy rate	□99%
Face recognition distance	0.3 to 1.5 m
Button	Physical call button
Power supply	12 VDC, 1 A, standard PoE
Working temperature	-30 °C to 65 °C (-22 °F to 149 °F)

Working humidity	0 to 90% (No condensing)
Dimensions	135mm ×52 mm × 26 mm (5.32" × 2.05" × 1.02")
Installation	Wall mounting
Protective level	IP65
Weight	Gross weight: 0.59 kg (1.3 lbs) Net weight: 0.19 kg (0.42lbs)
QR code recognition	Not support
Face anti-spoofing	Support
Two-way audio	Support

Specifications are summarised from the manufacturer's published information (checked 2026-10-07). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-door-access-ds-k1t323ebwx-e1.html>