Hikvision DS-K1T673DWX-PROE1

Pro Face Access Terminal · Specification summary



Operating System	Linux
Screen Size	7 inch
Screen Type	IPS, capacitive touch screen
Screen Resolution	600 × 1024
Video	Lens 2, Resolution 2 MP
Network Interface	1 RJ-45, 10/100/1000 M self-adaptive
Wi-Fi	Support, 2.4 G, 802.11b/g/n
PoE	Support, IEEE802.3at
Face Capacity	10,000
Fingerprint Capacity	10,000 (With fingerprint module)
Card Capacity	50,000
Event Capacity	150,000
Face Recognition Distance	0.3 to 3 m
Face Recognition Accuracy Rate	≥ 99%
Card Type	M1 card, Felica card, DESfire card
Power Supply	12 VDC to 24 VDC, 2 A
Working Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Protective Level	IP68, IK07
Dimensions	110.5 mm × 209.2 mm × 24 mm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-door-access-ds-k1t673dwx-proe1.html