Hikvision DS-K3G411

Tripod Turnstile · Specification summary



MCBF	> 3 million times
Lock control	2
Alarm input	2
Alarm output	2
Network interface	1
RS-485	6 (The interfaces can be switched to RS-232 via DIP switch)
RS-232	6 interfaces can be switched to RS-232 via DIP switch; 2 for fingerprint module or QR code scanner
Card capacity	60,000
Event capacity	180,000
Throughput	More than 35 persons per minute; The actual throughput is affected by the person passing rate and passing method
Power supply method	100 to 240 VAC; 50 to 60 Hz
Lane width (General)	550mm
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	0% to 95% (No condensing)
Dimensions	Without package: 502 mm × 202 mm × 1010 mm (19.8" × 8.0" × 40.0"); With package: 745 mm × 365 mm × 1120 mm (29.3" × 14.4" × 44.1")
Pedestal material	SUS304 stainless steel
Application environment	Indoor
Approval	CE/FCC/CB/RoHS/REACH/WEEE
Module selection	NO
Authentication mode	Card; Face; QR code; Fingerprint
Authentication exclusionary	Fingerprint; QR code
Card type	EM; M1
Wall distance	20mm
Lane width (Configuration)	550

Pedestal width	202 mm
Pedestal length	502 mm
Barrier material	Stainless steel pipe
Base	YES
Side pedestal	YES
Base model	DS-K3G411-BASE
Side pedestal type	fence(130mm)
Remote controller type	433 Mhz; 868 Mhz

Specifications are summarised from the manufacturer's published information (checked 2026-10-31). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-hikvision-turnstile-ds-k3g411.html