



Hikvision DS-KAD606

· Specification summary

Device class	Video/Audio Distributor
Ethernet interfaces	8 RJ45 10/100 Mbps interfaces; the model number is not an interface count.
Interface operation	Full/half duplex and MDI/MDI-X self-adaptive operation.
Network standards	IEEE 802.3, 802.3u and 802.3x; these entries are not proof of IEEE PoE output compliance.
Packet processing	Store-and-forward processing.
Flow control	IEEE 802.3x in full duplex; back pressure in half duplex.
Priority queues	4 priority queues, not 4 Ethernet ports or powered channels.
Power input	110 to 220 V AC, self-adaptive, as printed; check the actual rated nameplate and local electrical suitability.
Power consumption	Less than 6 W catalogue consumption; not a connected-device output budget.
Operating temperature	-15 to 55 °C in the cited historical reference; confirm the supplied revision and installation conditions.
Operating humidity	5% to 95%, non-condensing in the cited table; no additional enclosure or condensation protection inferred.
Manufacturer dimensions	268.6 x 118.4 x 102.2 mm in the manufacturer L x W x H notation; allow separate cable and mounting clearances.
Catalogue context	Listed in the manufacturer Video Intercom range; verify the exact connected stations and power design.

Specifications are summarised from the manufacturer's published information (checked 2026-10-20). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-door-access-ds-kad606.html>