



Hikvision DS-KAD704Y

· Specification summary



Device class	Two Wire Distributor
Distribution reference	2-wire IP distribution listed; confirm the exact door/indoor stations and compatible system revision
Device interfaces	Four 2-wire device interfaces with a power-supply function; compatible devices and channel ratings require separate verification
Cascade interfaces	Two cascade interfaces; the document names DS-KAD704Y, DS-KAD706Y and DS-KAD706Y-S series. Match the complete device revisions and configuration
Interface indicators	Six interface indicators
Network interface	One RJ-45 interface; network speed and protocol details are not established in this source
Reset button	One reset button
DC input	24 V DC input; input current and connected-device output limits require separate confirmation
Mounting	DIN-rail mounting listed; matched rail and installation fit need confirmation
Body-drawing reference	143.69 (W) × 90 (H) × 65.95 (D) mm in the body views; a separate 2.4 mm feature is marked. Confirm protrusions and full mounting clearance
Operating temperature	-10 to +55 °C manufacturer reference; match actual operating conditions
Operating humidity	10-90%, non-condensing
Optional power unit	Optional DS-KAW30-2N power-supply unit; not assumed included and no parent/adaptor ratings transferred
Optional bundle reference	Optional DS-KIS702Y-P two-wire IP bundle listed; bundle contents and device compatibility require separate confirmation

Specifications are summarised from the manufacturer's published information (checked 2026-10-15). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-door-access-ds-kad704y.html>