



Hikvision DS-KD7003EY-IME2/Aluminum

· Specification summary

Device class	2-wire HD Door Station
Housing material	Aluminium in the exact /Aluminum column; do not merge it with the stainless-steel bare model.
Field of view	133° horizontal and 82° vertical in the cited specification table.
Wide dynamic range	WDR support is listed; no numerical dB value established here.
Camera resolution	2 MP camera reference; no pixel dimensions or frame rate inferred.
Lock control	2 lock-control circuits are listed, not 2 included locks or confirmation of an electrical load rating.
Status indicators	4 LEDs: Opening Door, Calling, Intercom and In Use.
Call-button configuration	0 to 2 buttons with flexible configuration in the brochure; confirm the actual supplied assembly.
Protection reference	IP65 and IK08 reference ratings; confirm the complete assembled installation and sealing.
Manufacturer dimensions	99.5 x 98.5 x 35 mm in the source order; confirm mounting-frame and cable clearance.
Application environment	Outdoor application reference in the table; not an installed-system weatherproof guarantee.

Specifications are summarised from the manufacturer's published information (checked 2026-10-20). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-video-intercom-ds-kd7003ey-ime2-aluminum.html>