



Hikvision DS-KV6113-WPE1(C)

POE/Wifi Villa Door Station · Specification summary



Resolution	Main stream: 1920 × 1080p, 720p Sub stream: 640 × 480p
Weight	Net weight: 0.190 kg Gross weight: 0.414 kg
ROM	32 MB
RAM	256 MB
Lens	1
FOV	Horizontal: 131° Vertical: 78°
Operation system	Linux
Processor	Embedded high performance processor
Wide dynamic range (WDR)	Support 120 dB
Supplement light	IR light, up to 3 m
Video compression standard	H.264; h.265; MJPEG
Audio input	1 built-in omnidirectional microphone
Audio output	1 built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
User capacity	2000
Card capacity	10000
Wi-Fi	IEEE802.11b, IEEE802.11g, IEEE802.11n
Bluetooth	Not supported.
Network interface	1 RJ-45, 10/100 Mbps self-adaptive
TF card	Reserved
Lock control	1 relay, Max. 30 VDC 2 A
Button	1 physical button
Installation	Surface mounting
Protective level	IP65
Working temperature	-40 °C to 55 °C(-40 °F to 131 °F)

Working humidity	10% to 95% (no-condensing)
Dimension (W × H × D)	138 mm × 65 mm × 27 mm (5.4" × 2.6" × 1.1")
Application environment	Outdoor
Power consumption	□ 10 W
1	Microphone
2	Camera
3	Indicator
4	Button
5	Card Reading Area
6	Loudspeaker

Specifications are summarised from the manufacturer's published information (checked 2026-10-25). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-video-intercom-ds-kv6113-wpe1c.html>