



Hikvision DS-PDC10AM-VG3

· Specification summary

Detection Method	Passive Infrared
Detection Range	Wall Mount: 10 m Ceiling Mount: 6 m
Detection Angle	5°
Detection Zones	32
Detectable Speed	0.2 to 3 m/s
Sensitivity	Auto
White Light Filter	6500 lux
Digital Temperature Compensation	Supported
Creep Zone Protection	Supported
Anti-masking	Supported
Anti-masking Method	Active infrared
Digital Processing	Supported
Sealed Optics	Supported
Tamper Protection	Front, Rear
Directional Detection	Supported
Alarm Output	Normally Closed
LED Indicator	Blue(Alarm), Green+Orange(Mask)
Transmission Method	Wired
Power Consumption	22 mA Max
Power Supply	9 to 16 VDC
Typical Voltage	12 VDC
Operation Temperature	-25 °C to 60 °C
Storage Temperature	-25 °C to 60 °C
Operation Humidity	10% to 90%
IP Rate	IP65
Dimensions (W × H × D)	29.2 mm × 134.4 mm × 39.5 mm
Weight	77.5 g
Mounting Height	2 to 4 m
Mounting Method	Wall, Ceiling
Application Scenario	Indoor, Outdoor
Bracket	L-shaped adapter included

EOL Resistors

Selectable for alarm and tamper wiring

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-alarm-ds-pdc10am-vg3.html>