



Hikvision DS-PDC15-EG2

· Specification summary



Detection Method	Passive Infrared
Detection Range	15 m
Detection Angle	6.3°
Detection Zones	18
Detectable Speed	0.3 to 2 m/s
White Light Filter	6500 lux
Digital Temperature Compensation	Supported
Creep Zone Protection	Supported
PIR Sensor	Dual-element infrared sensor
Digital Processing	Supported
Sealed Optics	Supported
Tamper Protection	Front
Alarm Output	Normally Closed
LED Indicator	Blue(Alarm)
Transmission Method	Wired
Power Supply	9 - 16 VDC
Typical Voltage	12 VDC
Power Consumption	11 mA Max
Reverse-polarity Protection	Supported
Operation Temperature	-10 °C to 55 °C
Storage Temperature	-20 °C to 60 °C
Operation Humidity	10% to 90%
Dimensions (W × H × D)	65.4 mm × 86.8 mm × 45.5 mm
Weight	68 g
Mounting Height	2.4 m to 3.6 m
Mounting Method	Wall

Application Scenario	Indoor
Bracket	Optional wall & ceiling accessory
EOL Resistors	Selectable for alarm and tamper wiring

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-alarm-ds-pdc15-eg2.html>