



Hikvision DS-PDC5NC-EG2

· Specification summary

Detection Method	Passive Infrared
Detection Range	5 m
Detection Angle	5°
Detection Zones	28
Detectable Speed	0.3 to 2 m/s
Sensitivity	Auto
White Light Filter	6500 lux
Digital Temperature Compensation	Supported
Creep Zone Protection	Supported
Ceiling Curtain Coverage	Up to 5 m wide × 4 m high
Digital Processing	Supported
Tamper Protection	Front
Directional Detection	Supported
Alarm Output	Normally Closed
LED Indicator	Blue(Alarm)
Transmission Method	Wired
Power Consumption	15 mA Max
Power Supply	9 to 16 VDC
Typical Voltage	12 VDC
Operation Temperature	-10 °C to 55 °C
Storage Temperature	-20 °C to 60 °C
Operation Humidity	10% to 90%
Dimensions (W × H × D)	29.7 mm × 78.1 mm × 24.8 mm
Weight	31.5 g
Mounting Height	2.4 to 4 m
Mounting Method	Ceiling
Application Scenario	Indoor

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-alarm-ds-pdc5nc-eg2.html>