



Hikvision DS-PK1-E-WE

· Specification summary

Battery Type	Four AA batteries
Power Supply	Battery Supply
Operation Humidity	10% to 90% (No condensing)
Operation Temperature	-10 °C to +55 °C
Battery Life Span	Up to 2 years (standby time)
RF Frequency	868 MHz
RF Modulation	2GFSK
RF Distance	1200 m (open area)
RF Method	Two-way communication
Wireless Security	AES-128 encryption
Frequency Hopping	Supported
Installation method	Screw mounting
Dimensions (W × H × D)	140 × 86 × 22 mm
Weight	151 g without batteries
Arming Controls	Stay/away arm, disarm and clear alarms for selected or all areas
Emergency Keys	Fire, panic and medical alarms; silent or audible alarm selectable
Output Control	Supported
Remote Configuration	Through app
Keys and Backlight	Full touch keys with LED backlight
Area Indicator	LED indicates programmed area

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-alarm-ds-pk1-e-we.html>